

Rotor 8

- [Français](#)
- [English](#)

Downloadable files

×

Open access

[Git project](#)

Original model

Rotor 8 is part of a research program to study the effects of blade row solidity on efficiency and stall margin of an axial-flow compressor rotor. It is one of a series of rotors designed to further study the effects of solidity : rotor 8 with a tip solidity of 1.5, rotor 12 with a tip solidity of 1.7 and rotor 14 with a tip solidity of 1.3. Tip solidity are being changed by varying the number of blades while maintaining the same velocity diagrams and flow path. These stages were designed such that the tip solidity of both the rotor and stator blades are the same.

- Original technical report ^[1]:

```
@TechReport{osborn1973design,
  author      = {Osborn, Walter M. and Urasek, Donald C. and Moore,
R. D.},
  date       = {1973},
  institution = {NASA Lewis Research Center Cleveland, OH, United
States},
  title      = {Performance of a single-stage transonic compressor
with a blade-tip solidity of 1.5 and comparison with 1.3- and 1.7-solidity
stages},
  number     = {NASA-TM X-2926},
  url       = {https://ntrs.nasa.gov/citations/19740002621},
}
```

- Picture :




Fig1. <https://ntrs.nasa.gov/citations/19740002621> p.67

Useful documents

- [downloadable models](#) (Git project)
 - NASA technical report (.pdf)
 - geometrical parameters file (.csv), usable as input of OpenMCAD^[2] to generate reference blade models.

Reference blade

The **reference blade** is defined with multiple-circular arc profiles^[3] given in the original NASA report^[1]. Corresponding models are computed with the open-source code OpenMCAD^[2].

Geometry

The geometry of rotor 8 is described in the [original NASA report](#) by the following tables. The length are in centimeters and the angles in degrees.

TABLE IV. - BLADE GEOMETRY FOR ROTOR 8

| RP | PERCENT RADII | | | BLADE ANGLES | | | DELTA INC | CONE ANGLE |
|-----|---------------|--------|--------|--------------|-------|-------|-----------|------------|
| | SPAN | RI | RO | KIC | KTC | KOC | | |
| TIP | 0. | 25.082 | 24.701 | 62.92 | 60.67 | 52.34 | 2.49 | -9.298 |
| 1 | 5. | 24.568 | 24.193 | 61.67 | 59.64 | 51.79 | 2.72 | -8.836 |
| 2 | 10. | 24.021 | 23.685 | 60.41 | 58.43 | 51.04 | 2.98 | -7.644 |
| 3 | 30. | 21.754 | 21.653 | 55.93 | 52.88 | 46.27 | 4.06 | -1.996 |
| 4 | 43. | 20.287 | 20.383 | 53.47 | 49.53 | 41.81 | 4.74 | 1.771 |
| 5 | 45. | 19.989 | 20.129 | 52.99 | 48.87 | 40.74 | 4.88 | 2.542 |
| 6 | 48. | 19.690 | 19.875 | 52.52 | 48.23 | 39.60 | 5.01 | 3.325 |
| 7 | 50. | 19.388 | 19.621 | 52.06 | 47.59 | 38.38 | 5.15 | 4.114 |
| 8 | 53. | 19.085 | 19.367 | 51.60 | 46.97 | 37.09 | 5.28 | 4.908 |
| 9 | 70. | 16.891 | 17.589 | 48.50 | 42.58 | 26.07 | 6.19 | 10.851 |
| 10 | 90. | 14.175 | 15.557 | 45.39 | 39.25 | 6.42 | 7.05 | 18.759 |
| 11 | 95. | 13.447 | 15.049 | 44.77 | 38.97 | -0.40 | 7.20 | 20.972 |
| HUB | 100. | 12.700 | 14.541 | 44.22 | 38.93 | -7.94 | 7.32 | 23.205 |

| RP | BLADE THICKNESSES | | | AXIAL DIMENSIONS | | | |
|-----|-------------------|-------|-------|------------------|-------|-------|-------|
| | TI | TM | TO | ZIC | ZMC | ZTC | ZOC |
| TIP | 0.051 | 0.152 | 0.051 | 1.020 | 2.104 | 2.330 | 3.347 |
| 1 | 0.051 | 0.162 | 0.051 | 0.970 | 2.098 | 2.290 | 3.379 |
| 2 | 0.051 | 0.172 | 0.051 | 0.918 | 2.094 | 2.246 | 3.417 |
| 3 | 0.051 | 0.216 | 0.051 | 0.723 | 2.082 | 2.039 | 3.598 |
| 4 | 0.051 | 0.244 | 0.051 | 0.609 | 2.072 | 1.879 | 3.715 |
| 5 | 0.051 | 0.250 | 0.051 | 0.586 | 2.069 | 1.844 | 3.739 |
| 6 | 0.051 | 0.256 | 0.051 | 0.564 | 2.066 | 1.808 | 3.764 |
| 7 | 0.051 | 0.262 | 0.051 | 0.542 | 2.063 | 1.772 | 3.789 |
| 8 | 0.051 | 0.267 | 0.051 | 0.519 | 2.060 | 1.734 | 3.815 |
| 9 | 0.051 | 0.309 | 0.051 | 0.354 | 2.032 | 1.439 | 4.000 |
| 10 | 0.051 | 0.359 | 0.051 | 0.138 | 1.977 | 1.037 | 4.208 |
| 11 | 0.051 | 0.373 | 0.051 | 0.071 | 1.958 | 0.920 | 4.253 |
| HUB | 0.051 | 0.387 | 0.051 | 0.000 | 1.935 | 0.797 | 4.295 |

Aerodynamic design

| | unit | values |
|------------------|---------|--------|
| pressure ratio | [-] | 1.75 |
| mass flow | [kg/s] | 29.5 |
| tip speed | [m/s] | 423 |
| tip solidity | [-] | 1.5 |
| aspect ratio | [-] | 2.4 |
| number of blades | [-] | 49 |
| rotative speed | [rad/s] | 1686 |

Material properties

The material of rotor 8 is not defined in the original NASA report. A generic titanium Ti-6Al-4V is considered:

| | unité | valeurs |
|-----------------|----------------------|-----------|
| alloy | [-] | Ti-6Al-4V |
| Young's modulus | [GPa] | 108 |
| density | [kg/m ³] | 4400 |
| Poisson's ratio | [-] | 0.34 |
| yield stress | [GPa] | 0.824 |

CAD model

The CAD model is computed with the open source code OpenMCAD^[2].



pressure side

suction side

Natural frequencies

First three natural frequencies (with clamped root) for the mesh computed with OpenMCAD^[2]:

| Mode | Type | Natural angular frequency (rad/sec) | Natural frequency (Hz) |
|------|------|-------------------------------------|------------------------|
| 1 | 1B | 1779.57 | 283.228 |
| 2 | 2B | 6407.97 | 1019.86 |
| 3 | 1T | 8746.82 | 1392.1 |

Initial blade

The **initial blade** is defined with in-house LAVA parameters^[4] computed from the reference blade CAD model. The initial blade is usually used as starting point for an optimization process. Its geometry is

similar to the one of the reference blade.

Natural frequencies

First three natural frequencies (with clamped root)

- from the whole mesh:

| Mode | Type | Natural angular frequency (rad/sec) | Natural frequency (Hz) |
|------|------|-------------------------------------|------------------------|
| 1 | 1B | 1778.69 | 283.088 |
| 2 | 2B | 6413.56 | 1020.75 |
| 3 | 1T | 8747.83 | 1392.26 |

- from the reduced order model:

| Mode | Type | Natural angular frequency (rad/sec) | Natural frequency (Hz) |
|------|------|-------------------------------------|------------------------|
| 1 | 1B | 1778.75 | 283.098 |
| 2 | 2B | 6416.20 | 1021.17 |
| 3 | 1T | 8750.91 | 1392.75 |

Fichiers téléchargeables

x

Libre accès

[lien vers le projet Git](#)

À propos

Le rotor 8 fait partie d'un programme de recherche visant à étudier les effets de la solidité des rangées d'aubes sur l'efficacité et la marge de décrochage d'un rotor de compresseur à flux axial. Il fait partie d'une série de rotors conçus pour étudier plus profondément les effets de la solidité : le rotor 8 avec une solidité en tête de 1.5, le rotor 12 avec une solidité en tête de 1.7 et le rotor 14 avec une solidité en tête de 1.3. La solidité est modifiée en faisant varier le nombre d'aubes tout en conservant les mêmes triangles de vitesse et le même trajet d'écoulement. Ces étages ont été conçus de manière à ce que la solidité en tête du rotor et du stator soit la même.

- Rapport technique original ^[1]:

```
@TechReport{osborn1973design,
  author      = {Osborn, Walter M. and Urasek, Donald C. and Moore,
R. D.},
  date       = {1973},
  institution = {NASA Lewis Research Center Cleveland, OH, United
States},
  title      = {Performance of a single-stage transonic compressor
with a blade-tip solidity of 1.5 and comparison with 1.3- and 1.7-solidity
stages},
  number     = {NASA-TM X-2926},
```

```
url = {https://ntrs.nasa.gov/citations/19740002621},  
}
```

- Photographie :




Fig1. <https://ntrs.nasa.gov/citations/19740002621> p.67

Documents utiles

- [modèles téléchargeables](#) (lien vers projet Git)
 - rapport technique original de la NASA (.pdf)
 - fichier de paramètres géométriques (.csv), utilisable en entrée de OpenMCAD^[2] pour générer l'aube de référence

Aube de référence

L'**aube de référence** est définie par des profils de type arcs circulaires multiples^[3], donnés dans le rapport technique original de la NASA^[1]. Les modèles associés sont obtenus avec le code en libre accès OpenMCAD^[2].

Géométrie

La géométrie du rotor 8 est décrite dans le [rapport d'origine de la NASA](#) par les tableaux suivants. Les grandeurs sont en centimètres et en degrés.

TABLE IV. - BLADE GEOMETRY FOR ROTOR 8

| RP | PERCENT RADII | | BLADE ANGLES | | | DELTA | CONE ANGLE | |
|-----|---------------|--------|--------------|-------|-------|-------|------------|--------|
| | SPAN | RI | RO | KIC | KTC | KOC | | INC |
| TIP | 0. | 25.082 | 24.701 | 62.92 | 60.67 | 52.34 | 2.49 | -9.298 |
| 1 | 5. | 24.568 | 24.193 | 61.67 | 59.64 | 51.79 | 2.72 | -8.836 |
| 2 | 10. | 24.021 | 23.685 | 60.41 | 58.43 | 51.04 | 2.98 | -7.644 |
| 3 | 30. | 21.754 | 21.653 | 55.93 | 52.88 | 46.27 | 4.06 | -1.996 |
| 4 | 43. | 20.287 | 20.383 | 53.47 | 49.53 | 41.81 | 4.74 | 1.771 |
| 5 | 45. | 19.989 | 20.129 | 52.99 | 48.87 | 40.74 | 4.88 | 2.542 |
| 6 | 48. | 19.690 | 19.875 | 52.52 | 48.23 | 39.60 | 5.01 | 3.325 |
| 7 | 50. | 19.388 | 19.621 | 52.06 | 47.59 | 38.38 | 5.15 | 4.114 |
| 8 | 53. | 19.085 | 19.367 | 51.60 | 46.97 | 37.09 | 5.28 | 4.908 |
| 9 | 70. | 16.891 | 17.589 | 48.50 | 42.58 | 26.07 | 6.19 | 10.851 |
| 10 | 90. | 14.175 | 15.557 | 45.39 | 39.25 | 6.42 | 7.05 | 18.759 |
| 11 | 95. | 13.447 | 15.049 | 44.77 | 38.97 | -0.40 | 7.20 | 20.972 |
| HUB | 100. | 12.700 | 14.541 | 44.22 | 38.93 | -7.94 | 7.32 | 23.205 |

| RP | BLADE THICKNESSES | | | AXIAL DIMENSIONS | | | |
|-----|-------------------|-------|-------|------------------|-------|-------|-------|
| | TI | TM | TO | ZIC | ZMC | ZTC | ZOC |
| TIP | 0.051 | 0.152 | 0.051 | 1.020 | 2.104 | 2.350 | 3.347 |
| 1 | 0.051 | 0.162 | 0.051 | 0.970 | 2.098 | 2.290 | 3.379 |
| 2 | 0.051 | 0.172 | 0.051 | 0.918 | 2.094 | 2.246 | 3.417 |
| 3 | 0.051 | 0.216 | 0.051 | 0.723 | 2.082 | 2.039 | 3.598 |
| 4 | 0.051 | 0.244 | 0.051 | 0.609 | 2.072 | 1.879 | 3.715 |
| 5 | 0.051 | 0.250 | 0.051 | 0.586 | 2.069 | 1.844 | 3.739 |
| 6 | 0.051 | 0.256 | 0.051 | 0.564 | 2.066 | 1.808 | 3.764 |
| 7 | 0.051 | 0.262 | 0.051 | 0.542 | 2.063 | 1.772 | 3.789 |
| 8 | 0.051 | 0.267 | 0.051 | 0.519 | 2.060 | 1.734 | 3.815 |
| 9 | 0.051 | 0.309 | 0.051 | 0.354 | 2.032 | 1.439 | 4.000 |
| 10 | 0.051 | 0.359 | 0.051 | 0.138 | 1.977 | 1.037 | 4.208 |
| 11 | 0.051 | 0.373 | 0.051 | 0.071 | 1.958 | 0.920 | 4.253 |
| HUB | 0.051 | 0.387 | 0.051 | 0.000 | 1.935 | 0.797 | 4.295 |

Caractéristiques aérodynamiques

| | unités | valeurs |
|---------------------|---------|---------|
| taux de compression | [-] | 1,75 |
| débit massique | [kg/s] | 29,5 |
| vitesse en tête | [m/s] | 423 |
| solidité en tête | [-] | 1,5 |
| allongement | [-] | 2,4 |
| nombre d'aubes | [-] | 49 |
| vitesse de rotation | [rad/s] | 1686 |

Propriétés matériau

Le matériau original du rotor 8 n'est pas défini dans le rapport de la NASA. Un alliage de titane Ti-6Al-4v est considéré:

| | unité | valeurs |
|--|-------|---------|
| | | |

| | unité | valeurs |
|-------------------------------|--------------|----------------|
| alliage | [-] | Ti-6Al-4v |
| module d'Young | [GPa] | 108 |
| masse volumique | [kg/m3] | 4400 |
| coefficient de Poisson | [-] | 0,34 |
| limite élastique | [GPa] | 0,824 |

Modèle CAO

Le modèle CAO est obtenu avec OpenMCAD^[2].

intrados



extrados



Fréquences propres

Fréquences des trois premiers modes (noeuds du pied d'aube encastrés) pour le maillage obtenu avec OpenMCAD^[2] :

| Mode | Type | Pulsation propre (rad/sec) | Fréquence propre (Hz) |
|------|------|----------------------------|-----------------------|
| 1 | 1B | 1779,57 | 283,228 |
| 2 | 2B | 6407,97 | 1019,86 |
| 3 | 1T | 8746,82 | 1392,1 |

Aube initiale

L'**aube initiale** est définie par des paramètres spécifiques au LAVA^[4] obtenus à partir du modèle CAO de l'aube de référence. L'aube initiale est classiquement utilisée comme point de départ dans le cadre de procédures d'optimisation; sa géométrie est similaire à celle de l'aube de référence.

Fréquences propres

Fréquences des trois premiers modes (noeuds du pied d'aube encastés),

- pour le maillage complet :

| Mode | Type | Pulsation propre (rad/sec) | Fréquence propre (Hz) |
|------|------|----------------------------|-----------------------|
| 1 | 1B | 1778,69 | 283,088 |
| 2 | 2B | 6413,56 | 1020,75 |
| 3 | 1T | 8747,83 | 1392,26 |

- pour le modèle réduit :

| Mode | Type | Pulsation propre (rad/sec) | Fréquence propre (Hz) |
|------|------|----------------------------|-----------------------|
| 1 | 1B | 1778,75 | 283,098 |
| 2 | 2B | 6416,20 | 1021,17 |
| 3 | 1T | 8750,91 | 1392,75 |

1. ^{a, b, c, d} Osborn. «Performance of a single-stage transonic compressor with a blade-tip solidity of 1.5 and comparison with 1.3- and 1.7-solidity stage » 1973. [pdf](#)
2. ^{a, b, c, d, e, f, g, h} Kojtych S., Batailly A. «OpenMCAD, an open blade generator: from Multiple-Circular-Arc profiles to Computer-Aided Design model» 2022. [code en libre accès](#)
3. ^{a, b} Crouse *et al.* «A computer program for composing compressor blading from simulated circular-arc elements on conical surfaces » 1969. NASA-TN-D-5437. [pdf](#)
4. ^{a, b} Kojtych S. *et al.* «Methodology for the Redesign of Compressor Blades Undergoing Nonlinear Structural Interactions: Application to Blade-Tip/Casing Contacts » 2022. Journal of Engineering for Gas Turbines and Power, Vol. 145, No. 5. [pdf](#)

Document issu de la page wiki:

https://wiki.lava.polymtl.ca/public/modeles/rotor_08/accueil?rev=1679270129

Dernière mise à jour: **2023/04/05 08:59**