

# NASA Rotor 67

- [Français](#)
- [English](#)

This page contains various informations associated to one of the rotor 67 blade model used in LAVA publications.

Downloadable files

×

**Open access**

[Git project](#)

## Original model

- Original technical report <sup>[1]</sup>:

```
@TechReport{urasek1979design,
author      = {Urasek, D. C. and Gorrell, W. T. and Cunnan, W. S.},
title       = {Performance of two-stage fan having low-aspect-ratio first-
stage rotor blading},
institution = {NASA Lewis Research Center Cleveland, OH, United States},
note        = {NASA-TP-1493, url~:
\url{https://ntrs.nasa.gov/citations/19790018972}, 1979 (accessed
2021-09-09)}}}
```

- Pictures :

Fig 1. <https://catalog.archives.gov/id/17500553>

Fig 2. <https://catalog.archives.gov/id/17500556>

```
@Misc{huebler1977records,
author    = {Laity, D.},
title     = {Stage 67 rotor and stage 67 casing half stators mounted.
{R}ecords of the {N}ational {A}eronautics and {S}pace {A}dministration,
1903 - 2006. {P}hotographs relating to agency activities, facilities and
personnel, 1973 - 2013},
note      =
{\href{https://catalog.archives.gov/id/17500553}{https://catalog.archives.
gov/id/17500553}, 1980 (accessed 2021-09-09)}, % Fig 1
note      =
{\href{https://catalog.archives.gov/id/17500556}{https://catalog.archives.
gov/id/17500556}, 1980 (accessed 2021-09-09)}, % Fig 2}
```

}

## Finite element mesh

- Number of nodes: 20393
- Total number of elements: 6232
- Number of degrees of freedom: 59964
- Element type: quadratic pentahedron



[finite element mesh overview \(coarse mesh\) -](#)

LaTeX source files

- Number of nodes: 83393
- Total number of elements: 28560
- Number of degrees of freedom: 246960
- Element type: quadratic pentahedron



[finite element mesh overview \(refined mesh\) -](#)

LaTeX source files

## Material properties

- The original material of the rotor 67 is not defined in the NASA report
- Considered properties: Ti-6Al-4V, generic titanium:
  1. Young's modulus  $E = 108$  GPa
  2. density  $\rho = 4400$  kg/m<sup>3</sup>
  3. Poisson's ratio  $\nu = 0.34$
  4. yield stress  $\sigma_Y = 0.824$  GPa
- First three predicted natural frequencies (with clamped root) for the coarse mesh:
  1. 1B: 2040.7 rad/s / 324.8 Hz
  2. 2B: 6345.9 rad/s / 1010.0 Hz
  3. 1T: 10734.6 rad/s / 1708.5 Hz
- First three predicted natural frequencies (with clamped root) for the refined mesh:
  1. 1B: 2039.7 rad/s / 324.6 Hz
  2. 2B: 6340.6 rad/s / 1009.1 Hz
  3. 1T: 10735.0 rad/s / 1708.5 Hz

## Featured references from the LAVA

- *Stratégie numérique pour l'analyse qualitative des interactions aube/carter* <sup>[2]</sup> BibTeX  
x

```
@Article{colaitis2021thesis,  
  author = {Cola\{i}tis, Y.},  
  title = {{Stratégie numérique pour l'analyse qualitative des  
interactions aube/carter}},  
  year = {2021},  
  note = {\href{https://tel.archives-ouvertes.fr/tel-03318777}{oai:  
tel-03318777}},  
  abstract = {This thesis introduces a frequency-domain numerical  
methodology based on the harmonic balance method coupled to a predictor-  
corrector continuation algorithm for the qualitative analysis of blade-  
tip/casing contacts in aircraft engines. Unilateral contact and dry  
friction are taken into account through a regularized penalty law. In  
order to enhance the robustness of the methodology, attention is paid to  
the mitigation of the Gibbs phenomenon. To this end, the employed  
alternating frequency/time scheme features a Lanczos filtering so that  
spurious oscillations of the computed nonlinear contact forces become  
negligible. The proposed methodology is shown to be fully compatible with  
the numerical models used for existing industrial time integration  
strategies. The proposed numerical methodology is combined with a model  
reduction technique on several industrial blades (compressor and fan) as  
well as on a full 21-blades bladed disk. In order to assess the influence  
of both contact law regularization and Lanczos filtering, obtained results  
are thoroughly compared to an existing, state-of-the-art, time  
integration-based numerical strategy relying on a Lagrange multiplier-  
based approach for contact treatment that was previously confronted to  
experimental results. The presented results underline the very good  
agreement between the proposed methodology and the reference time  
integration numerical strategy. A local stability analysis of the computed  
solutions is also performed thanks to Floquet theory by means of both  
monodromy matrix computation and Hill's determinant solution. These  
results thus complement existing time integration-based results on blade-  
tip/casing contact, providing a much needed qualitative understanding of  
the interaction and an accurate estimation of the nonlinear resonance  
frequency. }}
```

Cette page contient diverses informations associées à l'un des modèles de l'aube NASA rotor 67 utilisé dans les publications du LAVA.

Fichiers téléchargeables

×

**Libre accès**

[lien vers le projet Git](#)

## Modèle original

- Rapport technique original <sup>[1]</sup>:

```
@TechReport{urasek1979design,  
author      = {Urasek, D. C. and Gorrell, W. T. and Cunnan, W. S.},  
title       = {Performance of two-stage fan having low-aspect-ratio first-  
stage rotor blading},  
institution = {NASA Lewis Research Center Cleveland, OH, United States},  
note        = {NASA-TP-1493, url~:  
\url{https://ntrs.nasa.gov/citations/19790018972}, 1979 (accessed  
2021-09-09)}
```

- Photographies :

Fig 1. <https://catalog.archives.gov/id/17500553> 

Fig 2. <https://catalog.archives.gov/id/17500556> 

```
@Misc{huebler1977records,  
author      = {Laity, D.},  
title       = {Stage 67 rotor and stage 67 casing half stators mounted.  
{R}ecords of the {N}ational {A}eronautics and {S}pace {A}dministration,  
1903 - 2006. {P}hotographs relating to agency activities, facilities and  
personnel, 1973 - 2013},  
note        =  
{\href{https://catalog.archives.gov/id/17500553}{https://catalog.archives.  
gov/id/17500553}, 1980 (accessed 2021-09-09)}, % Fig. 1  
note        =  
{\href{https://catalog.archives.gov/id/17500556}{https://catalog.archives.  
gov/id/17500556}, 1980 (accessed 2021-09-09)}, % Fig. 2  
}
```

## Maillage éléments finis

- Nombre de noeuds : 20393
- Nombre total d'éléments : 6232
- Nombre de degrés de liberté : 59964
- Type d'élément : pentaèdre quadratique

 aperçu du maillage éléments finis (maillage grossier) -

sources LaTeX

- Nombre de noeuds : 83393

- Nombre total d'éléments : 28560
- Nombre de degrés de liberté : 246960
- Type d'élément : quadratic pentahedron



[aperçu du maillage éléments finis \(maillage fin\) -](#)

sources LaTeX

## Propriétés matériau

- Le matériau original du rotor 67 n'est pas défini dans le rapport de la NASA
- Propriétés considérées : alliage de titane Ti-6Al-4v :
  1. Module d'Young  $E = 108$  GPa
  2. masse volumique  $\rho = 4400$  kg/m<sup>3</sup>
  3. coefficient de Poisson  $\nu = 0,34$
  4. limite élastique  $\sigma_Y = 0,824$  GPa
- Trois premiers modes prévus (noeuds de la base encastés) pour le maillage grossier :
  1. 1F : 2040,7 rad/s / 324,8 Hz
  2. 2F : 6345,9 rad/s / 1010,0 Hz
  3. 1T : 10734,6 rad/s / 1708,5 Hz
- Trois premiers modes prévus (noeuds de la base encastés) pour le maillage fin :
  1. 1B: 2039,7 rad/s / 324,6 Hz
  2. 2B: 6340,6 rad/s / 1009,1 Hz
  3. 1T: 10735,0 rad/s / 1708,5 Hz

## Références du laboratoire

- *Stratégie numérique pour l'analyse qualitative des interactions aube/carter* <sup>[2]</sup> BibTex  
x

```
@Article{colaitis2021thesis,
  author   = {Cola\{i}tis, Y.},
  title    = {{Stratégie numérique pour l'analyse qualitative des
interactions aube/carter}},
  year     = {2021},
  note     = {\href{https://tel.archives-ouvertes.fr/tel-03318777}{oai:
tel-03318777}},
  abstract = {This thesis introduces a frequency-domain numerical
methodology based on the harmonic balance method coupled to a predictor-
corrector continuation algorithm for the qualitative analysis of blade-
tip/casing contacts in aircraft engines. Unilateral contact and dry
friction are taken into account through a regularized penalty law. In
order to enhance the robustness of the methodology, attention is paid to
the mitigation of the Gibbs phenomenon. To this end, the employed
alternating frequency/time scheme features a Lanczos filtering so that
spurious oscillations of the computed nonlinear contact forces become
negligible. The proposed methodology is shown to be fully compatible with
```

the numerical models used for existing industrial time integration strategies. The proposed numerical methodology is combined with a model reduction technique on several industrial blades (compressor and fan) as well as on a full 21-blades bladed disk. In order to assess the influence of both contact law regularization and Lanczos filtering, obtained results are thoroughly compared to an existing, state-of-the-art, time integration-based numerical strategy relying on a Lagrange multiplier-based approach for contact treatment that was previously confronted to experimental results. The presented results underline the very good agreement between the proposed methodology and the reference time integration numerical strategy. A local stability analysis of the computed solutions is also performed thanks to Floquet theory by means of both monodromy matrix computation and Hill's determinant solution. These results thus complement existing time integration-based results on blade-tip/casing contact, providing a much needed qualitative understanding of the interaction and an accurate estimation of the nonlinear resonance frequency. }}

1. <sup>a, b</sup> Reid. «Performance of two-stage fan having low-aspect-ratio first-stage rotor blading » 1979. [pdf](#)
2. <sup>a, b</sup> Colaïtis. « Stratégie numérique pour l'analyse qualitative des interactions aube/carter » 2021. [oai](#)

Document issu de la page wiki:

[https://wiki.lava.polymtl.ca/public/modeles/rotor\\_67\\_ancien/accueil?rev=1663338061](https://wiki.lava.polymtl.ca/public/modeles/rotor_67_ancien/accueil?rev=1663338061)

Dernière mise à jour: **2023/04/05 08:59**